

CORNER NEON 1616 RGBW 16W/M IP67

NGA/LL/NF/1616/C/16/RGBW-30/67



LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

This Medium Output RGB Colour + White Neon Flex features an angled cross section and is designed for precision and architectural integration. It delivers clean transitions along angled surfaces while offering a blend of vivid colours and crisp white light to any space.

PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.
- The product is supplied with 5 mounting accessories per meter.
- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



TECHNICAL INFORMATION

Product Code	NGA/LL/NF/1616/C/16/RGBW-30/67
Product Group	Neon Flex
Bend Direction	Horizontal OR Vertical (not Dual)
Power Consumption	16W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	R: 108 G: 287 B: 65 W: 270 lm
Efficacy	68lm/W
Colour Temperature	RGBW(3000K)
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	50mm

Dimensions	W 16mm x H 16mm
Mounting Clip Dims.	L 14mm x W 16mm x H 16mm
Alternative Mounting	N/A
Bending Diameter	ø≥300mm
Cable Entry	End / Side / Rear
Max Run Length	10m
Control Gear	0-10 / DALI / DMX
IP Rating	IP67
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	90°
Protection Class	III

EUROPE & AMERICA HQ
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA