

# FUSION NEON O306H 10W/M 2700K IP65

NGA/LL/NF/0306/H/10/2700/65

LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION



This Low Output Neon Flex features a rectangular cross-section and is designed for flexibility and visual elegance. It delivers smooth, uniform illumination ideal for accent lighting and creative design applications.

## PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.

- The product is designed for direct push-fit installation into a recessed groove and is supplied with adhesive backing as standard.

- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



## TECHNICAL INFORMATION

Product Code	NGA/LL/NF/0306/H/10/2700/65
Product Group	Neon Flex
Bend Direction	Horizontal
Power Consumption	10W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	197 lm
Efficacy	20lm/W
Colour Temperature	2700K
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	25mm

Dimensions	W 3mm x H 6mm
Mounting Clip Dims.	N/A (Push-fit into 3mm groove)
Alternative Mounting	Adhesive Tape
Bending Diameter	ø≥30mm
Cable Entry	End / Side / Rear
Max Run Length	4m
Control Gear	On-Off / TRIAC / 0-10 / DALI / DMX
IP Rating	IP65
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	120°
Protection Class	III

**EUROPE & AMERICA HQ**  
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

**MENA REGION HQ**  
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA