

FUSION NEON 0506V 4W/M 3000K IP65

NGA/LL/NF/0506/V/4/3000/65



LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

This Low Output Neon Flex features a dome-top cross-section and is designed for flexibility and style. It delivers high-quality, uniform illumination that meets the demands of modern lighting applications.

PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.
- The product is supplied with 5 mounting accessories per meter as standard, or available with an aluminium mounting channel upon request.
- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



TECHNICAL INFORMATION

| | |
|--------------------|----------------------------|
| Product Code | NGA/LL/NF/0506/V/4/3000/65 |
| Product Group | Neon Flex |
| Bend Direction | Vertical |
| Power Consumption | 4W/m |
| Supply Voltage | 24V DC Constant Voltage |
| Lumen Output | 509 lm |
| Efficacy | 127lm/W |
| Colour Temperature | 3000K |
| CRI | Ra>90 |
| MacAdam Step | <3SDCM |
| Lifetime | 50000hrs |
| Cutting Interval | Free Cut |

| | |
|-----------------------|------------------------------------|
| Dimensions | W 5mm x H 6mm |
| Mounting Clip Dims. | L 20mm x W 6.8mm x H 5mm |
| Alternative Mounting | 1m Channel / Adhesive Tape |
| Bending Diameter | ø≥30mm |
| Cable Entry | End |
| Max Run Length | 7m |
| Control Gear | On-Off / TRIAC / 0-10 / DALI / DMX |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Operating Temperature | -40°C to 55°C |
| Beam Angle | 180° |
| Protection Class | III |

EUROPE & AMERICA HQ
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA