

FUSION NEON 0805V 10W/M 3000K IP65

NGA/LL/NF/0805/V/10/3000/65



LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

This Low Output Neon Flex features a dome-top cross-section and is designed for flexibility and style. It delivers high-quality, uniform illumination that meets the demands of modern lighting applications.

PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.
- The product is supplied with 5 mounting accessories per meter as standard, or available with an aluminium mounting channel upon request.
- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



TECHNICAL INFORMATION

Product Code	NGA/LL/NF/0805/V/10/3000/65
Product Group	Neon Flex
Bend Direction	Vertical
Power Consumption	10W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	1091 lm
Efficacy	109lm/W
Colour Temperature	3000K
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	Free Cut

Dimensions	W 8mm x H 5mm
Mounting Clip Dims.	L 20mm x W 9.8mm x H 5mm
Alternative Mounting	1m Channel / Adhesive Tape
Bending Diameter	ø≥30mm
Cable Entry	End
Max Run Length	7m
Control Gear	On-Off / TRIAC / 0-10 / DALI / DMX
IP Rating	IP65
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	180°
Protection Class	III

EUROPE & AMERICA HQ
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA