

FUSION NEON 2018H DYN 26W/M IP67 HE

NGA/LL/NF/2018/H/26/DYN/27-65/67/HE




LED SPECIFICATION SHEET

PRODUCT DESCRIPTION

This High Output Dynamic White Neon Flex features a rectangular cross-section and is designed for flexibility and visual elegance. It delivers smooth, uniform illumination while consuming less power, seamlessly transitioning between warm and cool whites.

PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.
- The product is supplied with 5 mounting accessories per meter as standard, or available with an aluminium mounting channel upon request.
- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



TECHNICAL INFORMATION

Product Code	NGA/LL/NF/2018/H/26/DYN/27-65/67/HE
Product Group	Neon Flex
Bend Direction	Horizontal
Power Consumption	26W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	27K: 788 65K: 881 MAX: 881 lm
Efficacy	68lm/W
Colour Temperature	2700K-6500K
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	83.3mm

Dimensions	W 20mm x H 18mm
Mounting Clip Dims.	L 30mm x W 20mm x H 10.5mm
Alternative Mounting	1m Channel / Bendable Channel
Bending Diameter	ø≥300mm
Cable Entry	End / Side / Rear
Max Run Length	3m
Control Gear	0-10 / DALI / DMX
IP Rating	IP67
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	120°
Protection Class	III

EUROPE & AMERICA HQ
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

MENA REGION HQ
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA