

# FUSION NEON 2526 DUAL 24W/M 2700K IP67

NGA/NF/WW/2526/W/25/VH/24/2700/67

LED SPECIFICATION SHEET

## PRODUCT DESCRIPTION




This High Output Neon Wall Washer features a rectangular cross section and a narrow beam angle. It delivers sharp, focused illumination that enhances architectural surfaces with clean, linear precision.

## PRODUCT NOTES

- Fusion Neon is typically supplied in custom cut lengths, but can also be supplied in reels up to a maximum length of 5m, with cables at both ends.

- The product is supplied with 5 mounting accessories per meter as standard, or available with an aluminium mounting channel upon request.

- When unreeling NGA's Neon Flex, two people must work together no more than 1.5 m apart. One supports the reel while the other feeds the Neon out for installation. This prevents twisting and protects the internal LEDs.



## TECHNICAL INFORMATION

Product Code	NGA/NF/WW/2526/W/25/VH/24/2700/67
Product Group	Neon Flex
Bend Direction	Dual
Power Consumption	24W/m
Supply Voltage	24V DC Constant Voltage
Lumen Output	1680 lm
Efficacy	70lm/W
Colour Temperature	2700K
CRI	Ra>90
MacAdam Step	<3SDCM
Lifetime	50000hrs
Cutting Interval	250mm

Dimensions	W 25mm x H 26mm
Mounting Clip Dims.	L 30mm x W 22.6mm x H 13mm
Alternative Mounting	1m Channel / Bendable Channel
Bending Diameter	ø≥400mm
Cable Entry	End / Side / Rear
Max Run Length	8m
Control Gear	On-Off / TRIAC / 0-10 / DALI / DMX
IP Rating	IP67
IK Rating	IK08
Operating Temperature	-40°C to 55°C
Beam Angle	25°
Protection Class	III

**EUROPE & AMERICA HQ**  
T: +44 (0) 1276 686175 | E: info@nogreyarea.co.uk

**MENA REGION HQ**  
T: +971 (0) 433 38300 | E: info@nogreyarea.me | www.no-grey-area.com

NGA